

**Honeywell**

Vista Series



The Vista family is a series of totally compatible control panels designed to support the easiest to use end-user interfaces available. Vista offers more flexibility & simpler programming along with features that customers want. As the world's largest manufacturer of electronic security products, Honeywell builds proven performance into everything we make. Combine this with the 5800 Series wireless transmitters, and you now have the most flexible, reliable and cost effective solutions for security and home/business control.

A blend of head turning style and sophisticated technology, the state of the art touchscreen keypad makes security system operation easier than ever – with graphics and simple prompts guiding you every step of the way. By just touching the graphics on the intuitive, easy to read touchscreen display, you can conduct a variety of everyday tasks with unprecedented ease.

Our products do more than keep you safe...they can improve household communication, make your home more comfortable and provide a level of simplicity and convenience you'll really appreciate. Best of all, they can enhance the quality of life.

With solid features and robust system capacities, you'll find Vista panels to be the ideal choice for all your installations.



Vista 12a/48a/120aP2 Features

| | | Vista 12A | Vista 48a | Vista 120aP2 |
|--|---|------------------|------------------|---------------------|
| SYSTEM CAPACITY | Maximum Zone Capacity | 22 | 48 | 128 |
| | Std. Hardwired Zones (w/zone doubling) | 6 (12) | 8 (16) | 9 |
| | Maximum Hardwired Expansion | 8 | 40 | 119 (V-Plex) |
| | Maximum Wireless Expansion | 16 | 40 | 127 |
| | Wireless Key zones (do not use Alarm zones) | 16 | 16 | - |
| | Partitions | 2 + common | 3 | 8 |
| | User Codes | 16 | 48 | 150 |
| | Event Log (Vista key added) | 254 | 254 | 224 (512) |
| | Keypads | 8 | 8 | 16 |
| | Maximum Number of Schedules | 8 | 32 | 20 |
| FALSE ALARM PREVENTION FEATURES | Exit Delay Reset | ✓ | ✓ | - |
| | Exit Delay Countdown | ✓ | ✓ | - |
| | Cross Zoning/Linked Zone | ✓ | ✓ | ✓ |
| | Alarm Verification - Fire | ✓ | ✓ | ✓ |
| | Swinger Shutdown | ✓ | ✓ | ✓ |
| | Unvacated Auto-Stay | ✓ | ✓ | - |
| | Alarm Cancel Verification | ✓ | ✓ | ✓ |
| SYSTEM CONFIGURATION | Printer Support Serial | - | - | ✓ |
| | Scheduling | ✓ | ✓ | ✓ |
| | Real Time Clock | ✓ | ✓ | ✓ |
| | Temporal Bell | ✓ | ✓ | ✓ |
| | Bell Supervision | ✓ | ✓ | ✓ |
| | On-Board Triggers | 2 | 2 | 0 |
| | Relays Supported | 4 | 16 | 96 |
| | X-10 Devices Supported | ✓ | ✓ | ✓ |
| | Double Balanced Zones | ✓ | ✓ | - |
| | Dynamic Zone types | 4 | 4 | - |
| ADDITIONAL FEATURES | Graphic Keypad Support | 2 | 2 | 3 |
| | Single Button Arming | ✓ | ✓ | ✓ |
| | Step Arming | ✓ | ✓ | - |
| | Exit count down timer | ✓ | ✓ | - |
| | Keyfob Arm / Disarm Strobe flash | ✓ | ✓ | - |
| | Quick Exit | ✓ | ✓ | - |
| | Keypad Macros | 2 | 4 | 4 |
| | Viewable Event Log at Keypad | ✓ | ✓ | ✓ |
| | Time & Date Display | ✓ | ✓ | - |
| | Auto Arm/Disarm | ✓ | ✓ | ✓ |
| | X10 Powerline carrier support | ✓ | ✓ | ✓ |
| CONVENIENCE FEATURES | Master Console | - | - | ✓ |
| | Global Arming | ✓ | ✓ | ✓ |
| | Cross Partitioning (goto) | ✓ | ✓ | ✓ |
| | "Night" Arming | ✓ | ✓ | - |
| | RF Supervision by Transmitter | ✓ | ✓ | ✓ |
| | Common Lobby Logic | ✓ | ✓ | ✓ |
| | Configurable Zone Type | ✓ | ✓ | - |
| | Keystswitch Arming | ✓ | ✓ | ✓ |
| | User Access Schedules | ✓ | ✓ | ✓ |
| | Output Device Schedules | ✓ | ✓ | ✓ |
| | Panel Linking | - | - | 8 Panels |
| | Access Control | - | - | 8 Doors |
| | Access Card holders | - | - | 250 |
| | Follow-me Dialling | ✓ | ✓ | - |
| | Daylight savings auto. clock adjustment | ✓ | ✓ | ✓ |
| | Up & About Feature | ✓ | ✓ | - |
| | Internet / Intranet Monitoring | ✓ | ✓ | ✓ |
| TECHNICAL SPECIFICATION | ALARM OUTPUT | 2 Amp | 2 Amp | 2.8 Amp |
| | Aux Oput | 700 mA | 700 mA | 750 mA |